

MVS 52X

MVS 52X



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [Freestanding Vacuum Chamber Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Chamber & Seal Bars	
Chamber Width x Length	20.00" x 21.00"
Height (Chamber + Dome/Lid = Total)	3.50" + 3.00" = 6.50"
Number of Seal Bars (removable)	2
Position of Seal Bars	Left & Right
Seal Bar Length	2 x 21.00"
Distance between Seal Bars	16.00"
4 mm Seal + 1 mm Cut-Off Seal	✓
Unique Waffle-Pattern Sealing	✓
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓
Performance	
Pump Type	Busch KB Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement @ 50Hz	20 m ³ /h
Free Air Displacement @ 60Hz	24 m ³ /h
Pump Power Rating	1 hp
Power Supply	208V / 3ph / 12.5A
Display & Controls	
Water Resistant Digital Display	✓
LED Full Description Display	✓
Electronic Millibar Sensor	✓
Customizable Programs	9
Operational Features	
Programmable Sealing Time	✓
Programmable Vacuum Time (%)	✓
Moisture Quick Stop	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓
Service	
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	25.00" x 31.00"
Height (Lid open/closed)	52.50" / 38.75"
Working Height	35.00"
Locking Casters	✓
Shipping Wt. (Pallet not included)	345lbs
Optional Seal Bars	
Wide Flat Seal (6mm + 1mm Cut-Off Seal)	✓
Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓
Top & Bottom Seal	✓
Optional Features	
Inert Gas Flush Kit	✓
Evacuation Filter Kit	✓
Tray for Liquids	✓
Taller Dome	-
230V Single Phase @ 50/60Hz	✓
208V Three Phase @ 50/60Hz	48 m ³ /h

*Depends on type of product, film and operator ability.
 Specifications may change without notice.