

Products / Machine Technologies / Vacuum Sealers / Double Chamber Vacuum Sealers / MVS 630X

MVS 630X

MVS 630X



Downloads

- ▶ [Product Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Chamber & Seal Bars

Chamber Width x Length	27.75" x 31.5"
Chamber Height	8"
Number of Seal Bars (lid mounted)	2
Position of Seal Bars	Front & Back
Seal Bar Length	2 x 25"
Distance between Seal Bars	22"
10 mm Seal	✓

Performance

Pump Type	Busch R5 Oil Rotary
Free Air Displacement @ 50Hz	100 m³/h
Free Air Displacement @ 60Hz	120 m³/h
Pump Power Rating	5 hp
Power Supply	208V / 3ph / 12.8A

Display & Controls

Post-Mounted Swivel Digital Display	✓
Water Resistant Digital Display (IP65)	✓
Customizable Programs	9

Operational Features

Programmable Sealing Time	✓
Gentle Air Return	✓
Extra Vacuum	✓
High Volume Density Plates	✓

Service

Indicating Display	✓
1 Year Limited Warranty	✓
2nd Year Conditional Warranty*	VP Program

Housing & Dimensions

Material	Stainless 304
Lid Type / Lid Spring Alignment	Swing Lid / Horizontal
Lid with Dual Handles	✓
Width x Length x Height (Display included)	70" x 32.5" x 55"
Width x Length x Height (Lid open, Display excluded)	62" x 32.5" x 49"
Working Height	33"
Locking Casters	✓
Floor Level Adjusters	✓
Machine Weight / Shipping Weight	750 / 1280 lbs

Optional Seal Bars

Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓

Optional Features

Inert Gas Flush Kit	✓
Excess Bag Cut-Off	✓
Extra Seal Pressure	✓

*Through a certified minipack america dealer.
 Specifications may change without notice.