

NEW



Pole Type

Bench Type

Specifications

Capacity (Dual Range):

0-15 lb x 0.005 lb, 15-30 lb x 0.01 lb

Display:

Operator: Color LCD, 7 in
Customer: Grayscale LCD, 7 in

Display Items:

Tare: Four-digits
Unit price: Six-digits
Weight: Five-digits
Total price: Six-digits

Preset Keys:

1980: 20 x 99 pages

Memory Capacity:

4MB

Communications:

Static TCP/IP 10/100 Base T Ethernet
Wireless WEP/WPA/WPA2

Interface:

USB port, back-up and restore only

Platter:

15.7 in x 10.8 in (398 x 275 mm)

Print Head:

Direct thermal 2.2 in head (56 mm)

Print Speed:

3.2 / 3.9 / 4.7 / 5.9 in/sec
(80 / 100 / 120 / 150 mm/sec)

Label Size:

Width: 1.5-2.5 in (38-64 mm)
Length: 1.5-7.9 in (38-200 mm)

Label Roll:

Inside diameter: 1.6 in (40 mm) min
Outside diameter: 3.9 in (100 mm) max

Label Backing Paper:

Width: Up to 2.6 in (66 mm)

Power Supply:

AC100-240V, 50/60 Hz

Power Consumption:

Stand-by: 50W,
In operation: 120W

Classification:

NTEP CC 07-099A2,
UL listed

Warranty:

One-year limited warranty



Ishida Uni-5

Price Computing Scale/Printer/Color Touchscreen

The Uni-5 Series packs many features into an attractive low profile, small footprint case. The 7 inch color touch panel is easy to master. The operator display consists of windows for tare, weight, unit price and total price.

The membrane keyboard contains standard function keys and can be customized to include PLU, tare, and category presets plus a large number of specialized functions. Icons identify connectivity status, printing mode, and USB port. The programmable color touchscreen can be configured with three key sizes and up-to twenty presets per page.

Operators can view virtual receipts, open tickets, and totals before printing. The bright grayscale customer display can scroll and flash advertising messages and images. The fast and easy side-loading direct thermal printer has a variable speed and backing re-winder to quickly switch between labels and receipts.

The Ishida Uni-5 Series includes Ethernet (100Mbps) for connection to PC and other scales.

Standard Features

- Large color touchscreen
- Dual-range weighing (0-15 lb x 0.005 lb/15-30 lb x 0.01 lb)
- Internal wireless communications
- Ethernet communications
- Up to 99 pages of speed keys
- Adjustable touchscreen viewing angle
- 77 tactile keys
- 4 MB of memory
- Grayscale LCD customer-side display
- Self-serve mode/operation
- 30+ selectable fixed bar code formats
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale

Uni-5 Countertop Types

PART #	MODEL	CAPACITY
119356	Uni-5 Bench with internal RF	15 lb x 0.005 lb/30 lb x 0.01 lb
119357	Uni-5 Pole with internal RF	15 lb x 0.005 lb/30 lb x 0.01 lb
WITH ELEVATED KEYBOARD AND DISPLAY		
119358	Uni-5 Single Printer with internal RF	15 lb x 0.005 lb/30 lb x 0.01 lb
Consult	Uni-5 Twin Printer with internal RF (includes Receipt Printer)	0-15 lb x 0.005 lb/15-30 lb x 0.01 lb



Elevated keyboard and displays