


XTRAVAC

Providing Quality with Economical Solutions



XtraVac • CM640 Vacuum Double Chamber Machine



Machine Information XtraVac CM640

Machine Material	All Stainless
Machine Style	Double Chamber
Amount of Sealbars	4
Sealbar length	25.1 in / 640 mm
Distance between sealbars	22 in / 580 mm
Vacuum pump	Busch 100 / 5 (m3 / hp)
Chamber height	8 in / 200 mm (optional 10 or 12 in)
Machine on wheels	Standard
Leveling Legs	Standard
Chamber Lid Movement	Spring Assisted Manual
Machine Dim	66.9 x 33.8 x 40.1 in 1700 x 860 x 1020 mm
Chamber Dim	32.6 x 26.7 x 8/10/12 in 830 x 680 x 200/245/305 mm
Machine controls	Digital/Programmable
Machine weight	424 kg / 930 lbs
Electrical Connection	220 V 3 ph/60hz, (optional 400 V 3 ph/50hz)
Shipping Weight	494 kg / 1089 lbs
Shipping Dimension	69.6 x 35.4 x 46.8 in 1770 x 900 x 1190 mm
Hot wire cut off	Optional
Gas Flush	Optional
Bi-active Sealing	Optional

FEATURES & BENEFITS:

XtraVac CM640 features solid UHMW height adjustable filler plates, & an oil-filled, rotary vane vacuum pump. The dual chamber, quad sealbar layout is a versatile choice, ideal for small to medium processors or retailers.

- Quad seal bars for increased output and flexibility
- Compact design ideal for small floor plans
- Programmable, digital controls
- 2 operation modes (vacuum, vacuum & gas)
- Double Seam sealing & Mechanical Cut optional
- 12-month warranty
- Spare Parts kit included

XTRAVAC

Providing Quality with Economical Solutions

A Division of the Inauen Group · Kansas City, MO
Tel. 800-728-2999 · Sales@XtraVac.com